

CLAIM AMENDMENTS

Please amend the claims (~~striking through~~ indicating deletion and underline indicating insertion) as follows:

1. (Currently Amended) A digital, wireless PC/PCS modem for communicating to a satellite link and relay wireless communication system, said modem comprising:

a PCMCIA card type configuration of a type associated with a laptop computer unit supporting a circuit board;

a modem integrated within said circuit board in communication with said PCMCIA card;

an antenna having a protective cap and tuned to a frequency corresponding wireless system for transmitting and receiving digital signals and sending them to said circuit board to be processed; said antenna attached to said modem using a swivel joint assembly that allows for said antenna to be rotated and aligned to provide optimum transmission and reception of digital signals unlimited with respect to a user's locale;

a swivel-based, independent micro camera rotatable 180°; ~~and~~

a microphone for converting a transmitted sound into a sound signal; and;

at least three tuner cards for providing a multi-task video screen split into a plurality of frames of equal dimension, wherein each of said frames providing for a specific functional operation, task or application.

2. (Cancel).

3. (Cancel).

4. (Currently Amended) The digital, wireless PC/PCS modem for communicating to a wireless communication system as described in Claim 1, wherein ~~said~~ a loudspeaker and said microphone are coupled to a microprocessor via an audio interface block.

5. (Currently Amended) The digital, wireless PC/PCS modem for communicating to a wireless communication system as described in Claim 1 3, wherein said modem includes an enclosure top held in place by a series of fastening means, and wherein said enclosure top is removable so as to allow for repair or adjustment of any internal electronic components located inside said modem.

6. (Previously Presented) The digital, wireless PC/PCS modem for communicating to a wireless communication system as described in Claim 5, wherein said modem has an electrical connector comprising a series of electrical contacts, wherein said electrical connector is of an arrangement as defined by computer industry for PCMCIA connections.

7. (Cancel).

8. (Currently Amended) The digital, wireless PC/PCS modem for communicating to a wireless communication system as described in Claim 1 7, wherein said tuner cards being nine in number, and wherein said frames being nine in number.

9. (Currently Amended) The digital, wireless PC/PCS modem for communicating to a wireless communication system as described in Claim 8 7, wherein said functional operations and transmissions include video, voice, text, fax, and viewing of satellite television broadcast; and wherein said functional operations and transmissions being simultaneously displayed via said multi-task video screen.

10. (Previously Presented) An integrated PC/PCS digital wireless modem for communicating to a wireless communication system, said modem comprising:

a PCMCIA card type configuration of a type associated with a laptop computer unit supporting a circuit board;

a modem integrated within said circuit board in communication with said PCMCIA card;

an antenna having a protective cap and tuned to a frequency of a corresponding wireless system for transmitting and receiving digital signals and sending them to a circuit board to be processed; said antenna attached to said modem using a swivel joint

assembly that allows for said antenna to be rotated and aligned to provide optimum transmission and reception of digital signals unlimited with respect to user's locale;

a swivel-based, independent micro camera rotatable 180°;

a microphone for converting a transmitted sound into a sound signal; and

a loudspeaker for generating an audible sound in response to reception of digital signals, and wherein said loudspeaker and said microphone are coupled to a microprocessor via an audio interface block; and

at least three tuner cards.

11. (Previously Presented) The integrated PC/PCS digital wireless modem for communicating to a wireless communication system as described in Claim 10, wherein said tuner cards being nine in number for providing a multi-task video screen split into nine frames of equal dimension, wherein each of said nine frames providing for a specific functional operation, task, or application such as video, voice, text, fax, and viewing of satellite television broadcast.

12. (Previously Presented) A method for satellite link and relay wireless communication utilizing a digital, wireless PC/PCS modem in combination with laptop computer unit or a personal home computer comprising:

Digital signals transmitted via satellite link and relay wireless system are received by an antenna and passed from said antenna through a series of line amplifiers, said

series of line amplifiers and a network switching element having an input buffer coupled therebetween, wherein said network switching element receives input from said PC/PCS modem, said switching network element having frequency/feedback along with channel/screen selection function flowing from said switching network bi-directionally to a multi-tuner where data is passed from said multi-tuner module to a microprocessor, wherein said data is then passed on to a universal asynchronous receiver transmitter via a first bi-directional path, wherein said universal asynchronous receiver transmitter being responsible for all data transfers from a computer system to the computer system's modem output system, whereby data transfer occurs between all modules through a series of parallel bus, a series of serial transmit bus and a series of serial receive bus.

13. (Previously Presented) The method for satellite link and relay wireless communication utilizing a digital, wireless PC/PCS modem in combination with laptop computer unit or a personal home computer described in Claim 12, further comprising a micro controller for aligning said data in a proper configuration to be processed by a voice, data, fax and video processor through a second parallel bus, second serial transmit bus and second serial receive bus, wherein said voice, data, fax and video processor includes a digital signal processing support module used as a prebuffer into a digital signal processor, and wherein said digital signal processor performs all necessary operations on said data, including handshake verification, through a series of

built-in algorithms.

14. (Cancel).